SeaLand® Holding Tank Accessories

Upgrade tank quality and performance

Diptube Kit

Removes waste through top of tank – eliminates stagnant waste from sitting in discharge line connected at bottom of tank.

- Prevents clogging; reduces tank residual
- Fits tanks up to 30 in. (762 mm) high
- Easy to install

ITEM	DESCRIPTION
385310660	Holding tank diptube kit

NozAll™ Pump-out Adapter

Provides airtight seal between rubber nozzle or cam-operated type pump-out station nozzle and most boats' waste deck pump-out fittings.

- Cleaner pump-outs eliminates need for messy water source to assure sufficient vacuum
- Three sizes accommodate most pump-out fitting threads

Determining which NozAll adapter will fit a deck pump-out fitting requires two simple measurements from the cap of the deck fitting.

- 1. Measure the outside diameter (0.D.) of the cap threads (A).
- 2. Count the number of threads per 1/4-in. of thread length (B). Multiply that number by 4 to determine threads per inch (TPI).
- 3. Use chart below to determine to which NozAll item number the measurements apply.

ITEM	DESCRIPTION - MPT SIZE and TPI	DECK FITTING CAP O.D.	THREAD COUNT PER 1/4-IN.
310343502	1-1/2 in. MPT (38 mm), 11.5 TPI (4.5 tpcm)	1-7/8 in. (48 mm) OD	2-3/4
310343503	1-1/4 in. MPT (32 mm), 11.5 TPI (4.5 tpcm)	1-5/8 in. (41 mm) OD	2-3/4
310343504	1-1/4 in. MPT (32 mm), 16 TPI (6.3 tpcm)	1-5/8 in. (41 mm) OD	4

Universal Level Indicator Kit

Permits easy upgrade from single to multiple level holding tank monitor system.

- Replaces individual TankWatch® probes
- Two probes lengths adjust to any tank size or desired indication level
- Integrates with any Dometic Tank Monitor system

ITEM	DESCRIPTION
385311253	Universal level indicator kit with 12-in. (305 mm) probe
385311254	Universal level indicator kit with 24-in. (610 mm) probe

TankSaver® Relief Valve

Protects holding tanks from excessive suction of dockside pumps during holding tank pump-out.

- Installs easily no sealant or spinweld required
- Excellent odor seal

ITEM	DESCRIPTION
313255247	TankSaver relief valve

Universal Clean-out Kit

Provides convenient access to tank interior for inspection and cleaning.

- Installs easily on any rigid tank material
- Includes 3-in. (76 mm) inspection port and cap,
 O-ring, gasket and stainless steel hardware

ITEM	DESCRIPTION
307238685	Universal holding tank clean-out kit





Universal Flange Kit

Allows Dometic Tank Monitor probe cap installation into existing holding tank.

- Creates 3-in. (76 mm) inspection port
- Includes threaded fitting, gasket and hardware



ITEN	ı	DESCRIPTION
3072	230272	Universal flange kit



