

LIVEWELL pumps



PRO BAITMASTER™ II LIVEWELL PUMPS



The SHURFLO PRO BAITMASTER™ II Heavy Duty Livewell/Washdown Pumps are excellent for live-well or washdown applications in harsh marine environments. The seamless motor shell and sealed switch protects the pump from splashed liquids. Self-priming and can run dry without damage. For tank size 35 gallons and under. Thermally protected. Ignition protected. **2 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-off Pressure
PRO BAITMASTER™ II	4648-153-A07 4648-153-E07	12 VDC Continuous Duty, Splash Proof, Sealed Motor, ignition Protected	12 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	4.0 GPM [15.1 LPM]	8	45 PSI [3.1 Bar]
PRO BAITMASTER™ II	4648-163-A07 4648-163-E07	24 VDC Continuous Duty, Splash Proof, Sealed Motor, ignition Protected	24 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	4.0 GPM [15.1 LPM]	5	45 PSI [3.1 Bar]



BAIT SENTRY™ LIVEWELL PUMPS



The Bait Sentry™ Livewell Pumps are designed for easy installation and trouble-free operation. Magnetic Drive technology eliminates unnecessary failures. Motors keep running after ingesting debris or even when running dry. Patented anti-airlock feature allows the pump to clear trapped air in rough water or when boat is anchored. Includes dual port for easy washdown pump connection. **3 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Tank Size (Gallons)	Dimensions	Port Size Inlet/Outlet	Flow Rate	Amps (Max.)
Bait Sentry™ 500 Magnetic Drive	1700-000-030 1700-001-030	12 VDC Continuous Duty, Ignition Protected, ISO 8846	30	4.93" x 7.85" [125 x 200mm]	3/4" Inlet NPT 3/4" Outlet BARB	500 GPH [1893 LPH]	1.75
Bait Sentry™ 800 Magnetic Drive	1700-010-030 1700-011-030		40	4.93" x 7.85" [125 x 200mm]	3/4" Inlet NPT 3/4" Outlet BARB	800 GPH [3028 LPH]	3.5
Bait Sentry™ 1100 Magnetic Drive (A)	1700-020-030 1700-021-030		60	4.93" x 7.85" [125 x 200mm]	3/4" Inlet NPT 1-1/8" Outlet BARB	1100 GPH [4164 LPH]	3.75



SHURFLO® HIGH FLOW LIVEWELL PUMPS



Heavy duty and built to last, SHURFLO's 1500 and 2000 GPH nylon livewell pumps offer a unique motor cooling system (patent pending) to ensure efficient performance and long life. Designed for large livewell applications and comes standard with 6' tinned wire assembly. **2 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Port Size Inlet/Outlet	Flow Rate	Amps (Max.)
Livewell 1500	358-001-00 358-001-10	Anti-Airlock, Tough Nylon Housing, Washdown Port Connection, Submersible, Tinned 6' Wire Assembly, Ignition Protected, ISO 8846	12 VDC	8.3" x 6.2" [210 x 157 mm]	1" Inlet NPT 1-1/8" Outlet BARB	1500 GPH [5678 LPH]	8
Livewell 2000	358-011-00 358-011-10		12 VDC	8.3" x 6.2" [210 x 157 mm]	1" Inlet NPT 1-1/8" Outlet BARB	2000 GPH [7570 LPH]	10
Livewell 1500	358-101-00 358-101-10		24 VDC	8.3" x 6.2" [210 x 157 mm]	1" Inlet NPT 1-1/8" Outlet BARB	1500 GPH [5678 LPH]	4
Livewell 2000	358-111-00 358-111-10		24 VDC	8.3" x 6.2" [210 x 157 mm]	1" Inlet NPT 1-1/8" Outlet BARB	2000 GPH [7570 LPH]	5

PIRANHA™ LIVEWELL PUMPS



CE

Smart. Reliable. Attractive. Efficient. Our tough, high density nylon housing and heavy duty water cooled motor give the SHURFLO Livewell Pumps unparalleled reliability. Patented anti-airlock feature allows the pump to clear trapped air in rough water or when the boat is anchored. The dual port fitting allows for easy washdown pump connections. **2 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Port Size Inlet/Outlet	Flow Rate	Amps (Max.)
Livewell 600	357-013-00 357-013-10	Removable Cartridge, Anti-Airlock, Tough Nylon Housing, Washdown Port Connection, Submersible, Tinned 6' Wire Assembly, Ignition Protected, ISO 8846	12 VDC	6.5" x 3.75" [165 x 95mm]	3/4" [19mm] Inlet 3/4" [19mm] Outlet	600 GPH [2270 LPH]	2
Livewell 800	357-113-00 357-113-10		12 VDC	6.5" x 3.75" [165 x 95mm]	3/4" [19mm] Inlet 3/4" [19mm] Outlet	800 GPH [3027 LPH]	4.5
Livewell 1100	357-103-00 357-103-10		12 VDC	6.5" x 3.75" [165 x 95mm]	3/4" [19mm] Inlet 1-1/8" [29mm] Outlet	1100 GPH [4163 LPH]	4.5



PIRANHA™ STRAIGHT PORT AERATOR PUMPS



CE

Smart. Reliable. Attractive. Efficient. Our tough, high density nylon housing and heavy duty water cooled motor give the SHURFLO Livewell Pumps unparalleled reliability. Patented anti-airlock feature allows the pump to clear trapped air in rough water or when the boat is anchored. **2 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Port Size Inlet/Outlet	Flow Rate	Amps (Max.)
Straight Port Aerator 600	357-012-00 357-012-10	Removable Cartridge, Anti-Airlock, Tough Nylon Housing, Submersible, Tinned 6' Wire Assembly, Ignition Protected, ISO 8846	12 VDC	9.5" x 3.75" [241 x 95mm]	3/4" [19mm] Inlet 3/4" [19mm] Outlet	600 GPH [2270 LPH]	2
Straight Port Aerator 800	357-112-00 357-112-10		12 VDC	9.5" x 3.75" [241 x 95mm]	3/4" [19mm] Inlet 3/4" [19mm] Outlet	800 GPH [3027 LPH]	4.5
Straight Port Aerator 1100	357-102-00 357-102-10		12 VDC	9.5" x 3.75" [241 x 95mm]	3/4" [19mm] Inlet 1-1/8" [29mm] Outlet	1100 GPH [4163 LPH]	4.5



PIRANHA™ ANGLED PORT AERATOR PUMPS



CE

Smart. Reliable. Attractive. Efficient. Our tough, high density nylon housing and heavy duty water cooled motor give the SHURFLO Livewell Pumps unparalleled reliability. Patented anti-airlock feature allows the pump to clear trapped air in rough water or when the boat is anchored. **2 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Port Size Inlet/Outlet	Flow Rate	Amps (Max.)
Angled Port Aerator 600	357-014-00 357-014-10	Removable Cartridge, Anti-Airlock, Tough Nylon Housing, Submersible, Tinned 6' Wire Assembly, Ignition Protected, ISO 8846	12 VDC	7" x 7.5" [178 x 191mm]	3/4" [19mm] Inlet 3/4" [19mm] Outlet	600 GPH [2270 LPH]	2
Angled Port Aerator 800	357-114-00 357-114-10		12 VDC	7" x 7.5" [178 x 191mm]	3/4" [19mm] Inlet 3/4" [19mm] Outlet	800 GPH [3027 LPH]	4.5
Angled Port Aerator 1100	357-104-00 357-104-10		12 VDC	7" x 7.5" [178 x 191mm]	3/4" [19mm] Inlet 1-1/8" [29mm] Outlet	1100 GPH [4163 LPH]	4.5



SHURFLO® LIVEWELL FILL VALVE

CE

Keep your bait alive. The SHURFLO Livewell Fill Valve creates an energized environment that "keeps your bait alive." The full port fittings (3/4" or 1-1/8") assure the amount of flow required is achieved and maintained. The adjustable flow valve allows you to adjust the water flow to your desired amount. **3 Year Warranty**

Name	Model # OEM/Aftermarket	Description
Livewell Fill Valve	330-010 *330-021	Nylon Construction, 3/4" Full Port, Low Profile Design
Livewell Fill Valve	330-000 *330-021	Nylon Construction, 1-1/8" Full Port, Low Profile Design



*includes both 3/4" and 1-1/8" Full Port Fittings