

DHT-L Series SeaLand® Holding Tanks

Ready-to-install convenience



Model DHT42L
Holding Tank System

“No Discharge” is no problem with new pre-assembled holding SeaLand tank systems. With five popular tank sizes, boatbuilders can easily outfit any boat in their line with a high-quality holding tank, and assure customers of long-lasting performance and efficiency.

Available in capacities of 11, 16, 23, 29, and 36 gallons, SeaLand’s five new holding tanks are pre-plumbed with inlet and discharge fittings, a vent fitting, inspection port and pressure relief valve. Each “plug ‘n play”-style tank is pressure-tested and ready to install – just bolt it down, fasten the hoses, and hit the water.

High-strength polyethylene tanks feature a heavy-duty wall thickness of 0.25-inch to maintain integrity even under high pressure, and to avoid permeation of tank wall with waste odor. Built-in mounting “feet” allow fast, secure bolting to the hull without restraining straps. Top-mounted inlet, discharge and vent fittings rotate to accommodate virtually any plumbing layout. Inlet and discharge fittings accommodate 1.5-inch ID sanitation hose, but can be adapted to other plumbing system dimensions. Also included with each tank are an extra inlet fitting, plug, sealing grommet and hose lubricant for easy hose attachment.

SeaLand DHT-L series holding tanks are sized to fit on the most popular boat models and lengths.

Key Benefits

- Pre-assembled with all required fittings and ports
- Five sizes to fit wide range of boat models
- Heavy-duty polyethylene tank withstands high pressure
- Tank walls resist waste odor permeation
- Specially designed discharge fittings are clog-free and minimize tank residual
- Five-year limited warranty against cracking or leaking

DHT-L Series Holding Tank System Technical Specifications

MODEL	DESCRIPTION	DIMENSIONS LxDxH	EMPTY WEIGHT
DHT42L	11-gallon/42-liter holding tank system	18.1 x 13.8 x 13.7 in. / 460 x 350 x 348 mm	12 lbs./5.4 kg
DHT61L	16-gallon/61-liter holding tank system	26.0 x 13.8 x 13.7 in. / 660 x 350 x 348 mm	17 lbs./7.7 kg
DHT88L	23-gallon/88-liter holding tank system	31.5 x 15.7 x 15.3 in. / 800 x 400 x 388 mm	22.5 lbs./10.2 kg
DHT110L	29-gallon/110-liter holding tank system	47.2 x 13.8 x 13.7 in. / 1200 x 350 x 348 mm	30.9 lbs./14 kg
DHT137L	36-gallon/137-liter holding tank system	47.2 x 15.7 x 15.3 in. / 1200 x 400 x 388 mm	32 lbs./14.5 kg

Notes:
 "H" dimension indicates height to top of pre-installed fittings. Specifications subject to change without notice.

Plumbing Connection Dimensions

INLET FITTING	1.5 in./38 mm ID sanitation hose or PVC pipe
OUTLET FITTINGS	1.5 in./38 mm ID sanitation hose or PVC pipe
VENT FITTING	0.625 in./16 mm ID vent hose
INSPECTION PORT	3 in./76 mm FPT

Specifications subject to change without notice.

Product Details

MATERIALS	Tank	Polyethylene, 0.25 in./6.3 mm min. thickness	
	Fittings	PVC, ABS	
COLOR	Tank	Natural	
	Fittings	White	
CONTENTS	1x holding tank	1x pressure relief valve	ACCESSORIES
	1x inlet fitting	1x inspection port, cap	1x inlet fitting
	1x vent fitting	2x hose lubricant, tubes	1x sealing grommet
	2x outlet fittings	1x instruction manual	1x plug

Dimensions

