

# FRESH WATER pumps



## AQUA KING™ II FRESH WATER PUMPS 2.0 GPM & 3.0 GPM



SHURFLO's AQUA KING™ II Junior and Standard Fresh Water Pumps' design was created with unique over-molded single-piece diaphragm and internal by-pass (3.0 version only), assuring long life and top performance in all plumbing systems. These fresh water automatic demand pumps are quiet and can run dry without damage. Sealed switch. Ignition protected. Thermally protected. 1/2" hose barb fittings are included (aftermarket models only). **3 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-Off Pressure
AQUA KING™ II Junior 2.0	4128-110-A04 4128-110-E04	Intermittent Duty Up to 2 Fixtures	12 VDC	8.2" x 4.9" x 4.1" [208 x 124 x 104mm]	2.0 GPM [7.6 LPM]	3.5	30 PSI [2.0 BAR]
AQUA KING™ II Standard 3.0	4138-111-A65 4138-111-E65	Intermittent Duty Multi-Fixture Application	12 VDC	8.2" x 4.9" x 4.1" [208 x 124 x 104mm]	3.0 GPM [11.35 LPM]	6.5	55 PSI [3.8 BAR]
AQUA KING™ II Standard 3.0	4138-131-A65 4138-131-E65	Intermittent Duty Multi-Fixture Application	24 VDC	8.2" x 4.9" x 4.1" [208 x 124 x 104mm]	3.0 GPM [11.35 LPM]	3.8	55 PSI [3.8 BAR]



## AQUA KING™ II FRESH WATER PUMPS 4.0



SHURFLO's AQUA KING™ II Premium Fresh Water Pumps are designed for boats with multi-fixtures providing "Just like home" shower pressure. A built in mechanical bypass function enables these pumps to operate at lower flow conditions with minimal cycling. Featuring heavy duty, seamless shell electro coated motors built to withstand the tough marine environment with o-ring sealed end bells and completely sealed wire entries. Sealed switch. Ignition protected. Thermally protected. 1/2" hose barb fittings are included (aftermarket models only). **3 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-Off Pressure
AQUA KING™ II Premium 4.0	4148-153-A75 4148-153-E75	Intermittent Duty Multi-Fixture Application	12 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	4.0 GPM [15.1 LPM]	10	55 PSI [3.8 BAR]
AQUA KING™ II Premium 4.0	4148-163-A75 4148-163-E75	Intermittent Duty Multi-Fixture Application	24 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	4.0 GPM [15.1 LPM]	5	55 PSI [3.8 BAR]



## AQUA KING™ II FRESH WATER PUMPS 5.0



SHURFLO's AQUA KING™ II Supreme Fresh Water Pumps are designed for boats with multi-fixtures providing "Just like home" shower pressure. A built in mechanical bypass function enables these pumps to operate at lower flow conditions with minimal cycling. Featuring heavy duty, seamless shell electro coated motors built to withstand the tough marine environment with o-ring sealed end bells and completely sealed wire entries. Sealed switch. Ignition protected. Thermally protected. 1/2" hose barb fittings are included (aftermarket models only). **3 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-Off Pressure
AQUA KING™ II Supreme 5.0	4158-153-A75 4158-153-E75	Intermittent Duty Multi-Fixture Application	12 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	5.0 GPM [18.9 LPM]	13	55 PSI [3.8 BAR]
AQUA KING™ II Supreme 5.0	4158-163-A75 4158-163-E75	Intermittent Duty Multi-Fixture Application	24 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	5.0 GPM [18.9 LPM]	7	55 PSI [3.8 BAR]

## HIGH FLOW SYSTEMS

CE

The most advanced systems available. These fully-automatic, quiet units deliver water smoothly and consistently. **3 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Flow Rate	Amps (Max.)	Shut-Off Pressure
HIGH FLOW SYSTEM	4558-153-E75 4558-153-E75	12 VDC High Flow System AQUA KING™ II Supreme 5.0 GPM and PRO BLASTER™ II Ultimate 5.0 GPM, Manifold assembly and Mounting Board	12 VDC	10.0 GPM [37.8 LPM]	13/11	55 PSI [3.8 BAR]
HIGH FLOW SYSTEM	4558-163-E75 4558-163-E75	24 VDC High Flow System AQUA KING™ II Supreme 5.0 GPM and PRO BLASTER™ II Ultimate 5.0 GPM, Manifold assembly and Mounting Board	24 VDC	10.0 GPM [37.8 LPM]	7/6	55 PSI [3.8 BAR]



## SLV PUMP

CE

This compact automatic demand pump offers durability and dependability making it ideal for low volume, intermittent duty applications. The SLV Pump self-primers up to 2.5 vertical feet while delivering 1.0 GPM. **1 Year Warranty**

Name	Model # OEM/Aftermarket	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-Off Pressure
SLV	105-003 105-013	Automatic Demand Pump	12 VDC	6.8" x 3.9" x 2.5" [170 x 100 x 60mm]	1.0 GPM [3.8 LPM]	2.5	30 PSI [2.0 BAR]



# WASHDOWN pumps

## BLASTER™ II WASHDOWN PUMPS

CE

SHURFLO's BLASTER™ II Washdown Pump design was created with a unique over-molded single-piece diaphragm, assuring long life and top performance in all marine washdown applications. The BLASTER™ II washdown automatic demand pumps are thermally protected and can run dry without damage. Sealed switch. Ignition protected. Fittings and nozzle included (aftermarket models only). **2 Year Warranty**

Name	Model # OEM/Aftermarket	Voltage	Dimension	Flow Rate	Amps (Max.)	Shut-Off Pressure
BLASTER™ II	4238-121-A07 4238-121-E07	12 VDC	9" x 4.9" x 4.1" [229 x 124 x 104mm]	3.5 GPM [13.2 LPM]	7.5	45 PSI [3.1 BAR]
BLASTER™ II	4238-141-A07 4238-141-E07	24 VDC	9" x 4.9" x 4.1" [229 x 124 x 104mm]	3.5 GPM [13.2 LPM]	3.5	45 PSI [3.1 BAR]

