

PRO TOUCH Series NEW

12V
24V
48V
40A → 150A

AC/DC battery chargers from 40A to 150A. The powerful solution for yachts and superyachts (offshore yachting), for commercial and military vessels, offshore platforms and other industrial applications. More than 25 000 units sold worldwide. Starting in 2019, all PRO units become “PRO TOUCH” as they include TOUCHVIEW, the best HMI on the market, as standard equipment

MAIN ASSETS

Super User-Friendly NEW

Starting in 2019 (Q1), all PRO units include TOUCHVIEW, the best HMI on the market, as standard equipment. For a perfect battery monitoring experience

SuperConnected

All PRO TOUCH Chargers are smart, “open” devices with standard CANbus J1939 interface. They are also NMEA-Ready (NMEA2000 option is available from one unit). All PRO TOUCH Chargers can therefore be connected to any modern onboard system

Safe&Transparent

All PRO TOUCH Chargers feature an integrated Control Panel which displays the charging curve and will warn you of any alarms (temperature, voltage, fuses issues)

Ultra-Efficient

PRO TOUCH Chargers deliver full power even at very high temperatures (up to 50°C/122°F). This “no derating” feature is quite unique on the market. These models are configured with automatic (115V/230V and 50Hz/60Hz) switchover, except for three versions (24V/80A, 24V/100A) which exclusively feature 230V

Robust+

With their marinized circuit boards, our PRO TOUCH Chargers are specifically designed for sustained commercial use and tough environment. They come in a solid, 100% high-grade aluminum casing



Nine versions available

PRO TOUCH 12.70	3 out	12V	70A	115/230V	128 mm x 346 mm x 358 mm	399445
PRO TOUCH 12.90	3 out	12V	90A	115/230V	128 mm x 346 mm x 358 mm	399450
PRO TOUCH 24.40	3 out	24V	40A	115/230V	128 mm x 346 mm x 358 mm	399460
PRO TOUCH 24.60	3 out	24V	60A	115/230V	128 mm x 346 mm x 358 mm	399470
PRO TOUCH 24.80	3 out	24V	80A	230V	128 mm x 346 mm x 358 mm	399477
PRO TOUCH 24.100	3 out	24V	100A	230V	196 mm x 346 mm x 358 mm	399480
PRO TOUCH 24.150	3 out	24V	150A	230V	243 mm x 356 mm x 407 mm	399186
PRO TOUCH 24.150T	3 out	24V	150A	230/400V	243 mm x 356 mm x 407 mm	399187
PRO TOUCH 48.50	1 out	48V	50A	230V	196 mm x 346 mm x 358 mm	399500

Option available for PRO TOUCH Series

NMEA2000 interface (available from 1 unit)

On request

Need to renew your battery banks?

Please check out our complete offer of marine Lead/Acid, Lead/Calcium, Gel and AGM batteries on pages 18-20